



EN 14785  
 BlmSchV Stufe 2  
 Regensburger BStV / Aachener BStV / Munchener BStV  
 ART.15a B-VG / Klimafonds / LRV  
 4 stelle DM.186 / Conto Termico 2.0



<b>(Max) nominal heat output</b>	<b>10.9 kW</b>
<b>Minimum heat output</b>	<b>2.5 kW</b>
<b>Efficiency at Max</b>	<b>90.7 %</b>
<b>Efficiency at Min</b>	<b>95.7 %</b>
<b>Energy Efficiency Class (A++ / G scale)</b>	<b>A+</b>
<b>Energy Efficiency Index (EEI)</b>	<b>121 %</b>
<b>Seasonal space heating energy efficiency (ηs)</b>	<b>80 %</b>
<b>Temperature of exhaust smoke at Max</b>	<b>180 °C</b>
<b>Temperature of exhaust smoke at Min</b>	<b>74 °C</b>
<b>Particulate/OGC / Nox (nominal at 13%O2)</b>	<b>13 - 4 - 133 mg/Nm3</b>
<b>CO at 13% O<sub>2</sub> at Min and at Max</b>	<b>0.051 - 0.005 %</b>
<b>CO<sub>2</sub> at Min and at Max</b>	<b>6.2 - 10.5 %</b>
<b>Recommended draught at Max power</b>	<b>10 Pa</b>
<b>Minimum draught allowed for minimum power</b>	<b>5 Pa</b>
<b>Mass of smoke at Min and at Max</b>	<b>2.9 - 7.4 g/sec</b>
<b>Hopper capacity</b>	<b>35 l</b>
<b>Fuel dimensions</b>	<b>Ø 6mm L 3 ÷ 40mm</b>
<b>Hourly consumption at Min and at Max</b>	<b>0.6 - 2.5 kg/h *</b>
<b>Autonomy at Min and at Max</b>	<b>38 - 9 h *</b>
<b>Heatable volume m3</b>	<b>198 - 311 - 545 **</b>
<b>Combustion air inlet</b>	<b>Ø 50 mm</b>
<b>Air inlet</b>	<b>80 cm2</b>
<b>Smoke outlet</b>	<b>Ø 80 mm</b>
<b>Nominal electrical power (EN 60335-1).</b>	<b>136 W (max 360 W)</b>
<b>Supply voltage and frequency</b>	<b>230 Volt / 50 Hz</b>
<b>Net weight</b>	<b>180 kg</b>
<b>Distance from combustible material (back/side/under)</b>	<b>250 mm / 100 mm / 500 mm</b>
<b>Distance from combustible material (front/ceiling)</b>	<b>1030 mm / 1000 mm</b>



\* Data that may vary depending on the type of pellets used.

\*\*Heatable volume based on the requested power per m3 (respectively 55-35-20 W/m3)